



DECK WIDTH - 102"

Capacity (Distributed)	70,000 lbs.
Concentrated Load	50,000 lbs. in 10'
Base Trailer Weight	19,000 lbs.
Frame Construction	Fabricated Perimeter design A-656 high tensile
Crossmembers	8" Crossmembers on 12" centers
Hitch	Fifthwheel King Pin type
King Pin Setting	18"
Swing Clearance	82"
Loaded Deck Height	35"
Load Angle	12 degrees
Deck Width	102"
Landing Gear	2 Speed 70,000 lb., 100,000 lb. static load
Load Securement	2-way Chain Slot/Stake Pocket alternating 2' centers
Hydraulic System	Wet kit PTO hydraulic operation with controls at gooseneck
Tool Compartment	2 each 36" in 5th wheel area
Winch	12,000 lb Hydraulic with controls at gooseneck
Axles	3 each 23,000 lb. capacity
Hubs	Oil bath, Hub piloted with outboard drums, 8 hole bolt circle
Brakes	12-1/4" x 7-1/2" full air brakes with spring brakes all axles, automatic slack adjusters, equipped with 2S2M anti-lock braking system
Drums	Steel Outboard type
Suspension	Ridewell Model 240 Air Ride with dump valve
Wheels	17.5" x 6.75" Uni-mount 8 on 275mm bolt circle
Tires	235/75R 17.5 radial load range H
Finish	5 stage pre-treatment with two component epoxy primer and two component urethane enamel topcoat, standard color white
Electrical	Trucklite modular system with rubber isolated, sealed beam LED lighting
Decking	1 3/4" oak with fasteners at all cross members
Various Options	Spare Tire, Apitong Decking, Traction Devices, D-rings, Belt Winches, Outriggers, Custom Paint & Detail, Self Contained Power Unit

Specifications are subject to change without notice

Quality Trailers From Gem State Manufacturing, Inc.

P.O. Box 987 ~ Caldwell ~ Idaho ~ 83606 ~ 1-800-447-0213 ~ 208-455-7551 ~ Fax: 208-455-7554

www.trailmax.com